

LASSCO

www.lassco.co.uk

THREE PIGEONS

LASSCO Three Pigeons

Milton Common,

Oxfordshire OX9 2JN

+44 (0)1844 277188

3pigeons@lassco.co.uk

BRUNSWICK HOUSE

30 Wandsworth Road,

London SW8 2LG

+44 (0) 20 7394 2100

brunswick@lassco.co.uk



RECLAIMED 6" AND 4 5/8" VICTORIAN PINE FLOORBOARDS (15SQ M EX PLOWDEN ARMS)

salvaged from The Plowden Arms near Henley-on-Thames - BATCH SALE: 15 square metres the parcel,

Good grain, square edge boards, lay the varying widths in alternating courses to recreate a more characterful finish Condition: dark patina, pleasantly worn - wear, dinks and paint commensurate with age, this batch has not been previously picked from - good variety of lengths

DIMENSIONS: 15.5cm (6") Wide, 0.2cm (0") Thick, (two board widths - 12cm and 15.5cm), various lengths

PRICE: £1,100 the batch (incl VAT)

STOCK CODE: 45934



HISTORY

Square-edged in a mixture of lengths, as salvaged. The old growth Baltic Pine from which these boards are made is straight grained and with a mellow pale yellow colour if sanded. These boards are supplied unfinished and they require cleaning, sanding and finishing for those not celebrating the old patina.

Batch sale only (equiv price when sold per sq m = £1280)

The Building Conservation Society sums up the case for reclaimed pine flooring:

“The record demand for house building in 18th and 19th century London was an indicator of the nation’s prosperity. The demand for buildings resulted in a demand for timber; that timber was pine, felled in Poland and sent to England through the Baltic ports. The soaring popularity of imported softwood was driven by its quality and availability as well as favourable transport and conversion costs. The quality of slow-grown old-stand timber such as Pinus Sylvestris that was cut inland and sent down river to the Baltic ports of Memel and Riga was recognised by architects and craftsmen of the period. Contemporary specifications (for example by English architect Sir John Soane) called for pine and fir from these ports, including Memel and Riga Fir.

Much of our historic joinery and flooring was constructed from wood that was slow grown. This wood generally has a fine, close-grained texture and, because much of it was from old stands, it tends to be fairly clear of knots and vertically grained, giving it good durability and stability.

Today, managed softwood plantations aim to produce timber as quickly and as economically as possible. This faster grown timber is not as durable as that from the mature trees that were more common up to the start of the 20th century. Much of the modern fast-grown softwood will be used in construction once it has been pressure impregnated with preservatives. Generally this type of timber is not suited to quality repairs of historic joinery. The quality and closeness of grain of repair timber should match that of the original as closely as possible. This will reduce differential movement at the junction of old and new wood.”